

# PRODUCT OVERVIEW

## Cable Tension Sets

The function of a cable tension set is to prevent the lifting cable running off the cable drum when the shaft operation is activated on power operated doors.

With normal lift and low headroom-systems, the open door has the panels horizontally. There is no weight in the vertical tracks so the door panel will not move down when shaft is activated.

This will result in rolling out the lifting cables without moving the door panel with the risk of cables running off the drums.

Below is an overview of the various cable tension set that FlexiForce has in its program.

DISCONTINUED  
PRODUCT



### 685CH

The 685CH will soon be discontinued because our supplier has indicated that they no longer produce this cable tension set.

If you wish to continue with the cable outside, you can switch to the 680 cable tension set.

NL

ISC-LHR

Cable out of reach

Cable outside

X

X



### 680

The cable run is to the bottom of the doorleaf on the outside of the track. We consider this to be "old" technique.

X

X



### 687

With the 687 the run of the cable is to the top of the doorleaf, so the cable is out of reach. We consider this to be the current technical standard.

X

X



### 687-2C

The 687-2C is the technical advanced version of the 687. This set is suitable for all NL drums, including FFNL32. We recommend using this product at NL systems

X

X



### 686C

This cable tension set is for ISC-LHR systems. Easy mounting on 686TR/L trailer

X

X